SAFETY DATA SHEET

(REACH regulation (EC) n° 1907/2006 - n° 2015/830)

SECTION 1 : IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product name : WYRITOL ANTI ACARIEN AEROSOL 500 ML Product code : 56073201.

1.2. Relevant identified uses of the substance or mixture and uses advised against N/A

1.3. Details of the supplier of the safety data sheet

Registered company name : PROVEN ORAPI.

Address : 225; Allée des Cèdres.01150.SAINT VULBAS .FRANCE.

Telephone : 0 810 400 402. Fax : 04 92 13 30 32.

FDS@orapi.com

1.4. Emergency telephone number : +33 (0)1 45 42 59 59.

Association/Organisation : INRS / ORFILA http://www.centres-antipoison.net.

SECTION 2 : HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

In compliance with EC regulation No. 1272/2008 and its amendments.

Aerosol, Category 1 (Aerosol 1, H222 - H229).

Repeated exposure may cause skin dryness or cracking (EUH066).

Specific target organ toxicity (single exposure), Category 3 (STOT SE 3, H336).

Hazardous to the aquatic environment - Chronic hazard, Category 2 (Aquatic Chronic 2, H411).

2.2. Label elements

Biocidal mixture (see section 15). Mixture for aerosol application.

In compliance with EC regulation No. 1272/2008 and its amendments.

Hazard pictograms :



GHS09 GHS07 GHS02

Signal Word :	
DANGER	
Product identifiers : EC 931-254-9	HYDROCARBURES, C6, ISOALCANES, <5% N-HEXANE
Hazard statements :	
H222	Extremely flammable aerosol.
H229	Pressurised container: May burst if heated.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.
Precautionary statement	ts - General :
P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
Precautionary statement	ts - Prevention :
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P271	Use only outdoors or in a well-ventilated area.

Precautionary statements - Res	sponse :				
P312	Call a POISON CENTER or doctor/physician if you feel unwell.				
Precautionary statements - Sto	orage :				
P410 + P412	Protect from sunlight. Do no expose to temperatures exceeding 50 oC/122oF.				
Precautionary statements - Disposal :					
P501	Dispose of contents and packaging in accordance with current regulations. The contaminated packaging and unused product should be disposed of with household waste.				

2.3. Other hazards

The mixture does not contain substances classified as 'Substances of Very High Concern' (SVHC) $\geq 0.1\%$ published by the European CHemicals Agency (ECHA) under article 57 of REACH: http://echa.europa.eu/fr/candidate-list-table The mixture satisfies neither the PBT nor the vPvB criteria for mixtures in accordance with annexe XIII of the REACH regulations EC 1907/2006.

SECTION 3 : COMPOSITION/INFORMATION ON INGREDIENTS

3.2. Mixtures

Composition :			
Identification	(EC) 1272/2008	Note	%
EC: 931-254-9	GHS09, GHS07, GHS08, GHS02		$50 \le x \% \le 100$
REACH: 01-2119484651-34	Dgr		
HYDROCARBURES, C6, ISOALCANES, <5% N-HEXANE	Flam. Liq. 2, H225		
INDEX: 601-004-00-0	GHS02, GHS04	С	$50 \le x \% \le 100$
CAS: 106-97-8	Dgr	[1]	50 × A/0 × 100
EC: 203-448-7	Flam. Gas 1, H220	[7]	
REACH: 01-2119474691-32		[/]	
REACH. 01-21194/4091-32			
BUTANE			
INDEX: 601-003-00-5	GHS02, GHS04	[1]	$10 \le x \% \le 25$
CAS: 74-98-6	Dgr	[7]	
EC: 200-827-9	Flam. Gas 1, H220	L' J	
REACH: 01-2119486944-21			
PROPANE			
INDEX: 601-004-00-0	GHS02, GHS04	С	$2.5 \le x \% \le 10$
CAS: 75-28-5	Dgr	[1]	
EC: 200-857-2	Flam. Gas 1, H220	[7]	
REACH: 01-2119474691-32			
AND ISOBUTANE			
CAS: 26046-85-5	GHS09		$0 \le x \% \le 2.5$
EC: 247-431-2	Wng		
	Aquatic Acute 1, H400		
1R-TRANS-PHENOTHRINE	M Acute = 1		
	Aquatic Chronic 1, H410		
	M Chronic $= 100$		
CAS: 1166-46-7	GHS09		$0 \le x \% \le 2.5$
EC: 214-619-0	Wng		
	Aquatic Acute 1, H400		
D-TRANS-TETRAMETHRINE	M Acute = 100		
	Aquatic Chronic 1, H410		
	M Chronic = 100		

Information on ingredients :

[7] Propellant gas

[1] Substance for which maximum workplace exposure limits are available.

SECTION 4 : FIRST AID MEASURES

As a general rule, in case of doubt or if symptoms persist, always call a doctor.

NEVER induce swallowing by an unconscious person.

4.1. Description of first aid measures

In the event of exposure by inhalation :

In the event of massive inhalation, remove the person exposed to fresh air. Keep warm and at rest.

If the person is unconscious, place in recovery position. Notify a doctor in all events, to ascertain whether observation and supportive hospital care will be necessary.

If breathing is irregular or has stopped, effect mouth-to-mouth resuscitation and call a doctor.

In the event of splashes or contact with eyes :

Wash thoroughly with soft, clean water for 15 minutes holding the eyelids open.

In the event of splashes or contact with skin :

Remove contaminated clothing and wash the skin thoroughly with soap and water or a recognised cleaner.

Watch out for any remaining product between skin and clothing, watches, shoes, etc.

If the contaminated area is widespread and/or there is damage to the skin, a doctor must be consulted or the patient transferred to hospital.

In the event of swallowing :

In the event of swallowing, if the quantity is small (no more than one mouthful), rinse the mouth with water and consult a doctor.

Keep the person exposed at rest. Do not force vomiting.

Seek medical attention, showing the label.

If swallowed accidentally, call a doctor to ascertain whether observation and hospital care will be necessary. Show the label.

4.2. Most important symptoms and effects, both acute and delayed

No data available.

4.3. Indication of any immediate medical attention and special treatment needed

No data available.

SECTION 5 : FIREFIGHTING MEASURES

Flammable.

Chemical powders, carbon dioxide and other extinguishing gas are suitable for small fires.

5.1. Extinguishing media

Keep packages near the fire cool, to prevent pressurised containers from bursting.

Suitable methods of extinction

In the event of a fire, use :

- sprayed water or water mist
- water with AFFF (Aqueous Film Forming Foam) additive
- halon
- foam
- multipurpose ABC powder
- BC powder
- carbon dioxide (CO2)

Prevent the effluent of fire-fighting measures from entering drains or waterways.

Unsuitable methods of extinction

In the event of a fire, do not use :

- water jet

5.2. Special hazards arising from the substance or mixture

A fire will often produce a thick black smoke. Exposure to decomposition products may be hazardous to health. Do not breathe in smoke.

In the event of a fire, the following may be formed :

- carbon monoxide (CO)
- carbon dioxide (CO2)

5.3. Advice for firefighters

Fire-fighting personnel are to be equipped with autonomous insulating breathing apparatus.

SECTION 6 : ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Consult the safety measures listed under headings 7 and 8.

For non first aid worker

Because of the organic solvents contained in the mixture, eliminate sources of ignition and ventilate the area.

Avoid inhaling the vapors.

Avoid any contact with the skin and eyes.

If a large quantity has been spilt, evacuate all personnel and only allow intervention by trained operators equipped with safety apparatus.

For first aid worker

First aid workers will be equipped with suitable personal protective equipment (See section 8).

6.2. Environmental precautions

Contain and control the leaks or spills with non-combustible absorbent materials such as sand, earth, vermiculite, diatomaceous earth in drums for waste disposal.

Prevent any material from entering drains or waterways.

If the product contaminates waterways, rivers or drains, alert the relevant authorities in accordance with statutory procedures

Use drums to dispose of collected waste in compliance with current regulations (see section 13).

6.3. Methods and material for containment and cleaning up

Clean preferably with a detergent, do not use solvents.

6.4. Reference to other sections

No data available.

SECTION 7 : HANDLING AND STORAGE

Requirements relating to storage premises apply to all facilities where the mixture is handled.

7.1. Precautions for safe handling

Always wash hands after handling.

Remove and wash contaminated clothing before re-using.

Ensure that there is adequate ventilation, especially in confined areas.

Remove contaminated clothing and protective equipment before entering eating areas.

Fire prevention :

Handle in well-ventilated areas.

Vapours are heavier than air. They can spread along the ground and form mixtures that are explosive with air.

Prevent the formation of flammable or explosive concentrations in air and avoid vapor concentrations higher than the occupational exposure limits.

Do not spray on a naked flame or any incandescent material.

Do not pierce or burn, even after use.

Use the mixture in premises free of naked flames or other sources of ignition and ensure that electrical equipment is suitably protected.

Keep packages tightly closed and away from sources of heat, sparks and naked flames.

Do not use tools which may produce sparks. Do not smoke.

Prevent access by unauthorised personnel.

Recommended equipment and procedures :

For personal protection, see section 8.

Observe precautions stated on label and also industrial safety regulations.

Do not breathe in aerosols.

Avoid inhaling vapors. Carry out any industrial operation which may give rise to this in a sealed apparatus.

Provide vapor extraction at the emission source and also general ventilation of the premises.

Also provide breathing apparatus for certain short tasks of an exceptional nature and for emergency interventions.

In all cases, recover emissions at source.

Packages which have been opened must be reclosed carefully and stored in an upright position.

Prohibited equipment and procedures :

No smoking, eating or drinking in areas where the mixture is used.

Never open the packages under pressure.

7.2. Conditions for safe storage, including any incompatibilities

No data available.

Storage

Keep out of reach of children.

Keep the container tightly closed in a dry, well-ventilated place.

Keep away from all sources of ignition - do not smoke.

Keep well away from all sources of ignition, heat and direct sunlight.

The floor must be impermeable and form a collecting basin so that, in the event of an accidental spillage, the liquid cannot spread beyond this area.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C.

Packaging

Always keep in packaging made of an identical material to the original.

7.3. Specific end use(s)

No data available.

SECTION 8 : EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

Occupational exposure limits :

- ACGIH TLV (American Conference of Governmental Industrial Hygienists, Threshold Limit Values, 2010) :

CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :	
106-97-8	1000 ppm	-	-	-	-	
74-98-6	1000 ppm	-	-	-	-	
75-28-5	1000 ppm	-	-	-	-	
- Germany - AGW (BA	4uA - TRGS 900	, 21/06/2010) :				
CAS	VME :	VME :	Excess	Notes		
106-97-8	1000 ml/m3	2400 mg/m3	4(II)	DFG		
74-98-6	1000 ml/m3	1800 mg/m3	4(II)	DFG		
75-28-5	1000 ml/m3	2400 mg/m3	4(II)	DFG		
- France (INRS - ED9	84 :2008) :					
CAS	VME-ppm :	VME-mg/m3:	VLE-ppm :	VLE-mg/m3 :	Notes :	TMP No :
CAS 106-97-8	VME-ppm : 800	VME-mg/m3 : 1900	VLE-ppm : -	VLE-mg/m3 :	Notes : -	TMP No : -
	800	e	VLE-ppm : -	VLE-mg/m3 : -	Notes : -	TMP No : -
106-97-8	800 2009) :	e	-	-	Notes : - Temps :	TMP No : - RSB :
106-97-8 - Switzerland (SUVA	800 2009) :	1900	-	-	-	-
106-97-8 - Switzerland (SUVA CAS	800 2009) : VME-mg/m3 :	1900 VME-ppm :	- VLE-mg/m3 :	-	-	-
106-97-8 - Switzerland (SUVA CAS 106-97-8	800 2009) : VME-mg/m3 : 1900	1900 VME-ppm : 800	- VLE-mg/m3 : -	- VLE-ppm : -	- Temps : -	-
106-97-8 - Switzerland (SUVA CAS 106-97-8 74-98-6	800 2009) : VME-mg/m3 : 1900 1800 1900	1900 VME-ppm : 800 1000 800	- VLE-mg/m3 : - 7200	- VLE-ppm : -	- Temps : -	-
106-97-8 - Switzerland (SUVA CAS 106-97-8 74-98-6 75-28-5	800 2009) : VME-mg/m3 : 1900 1800 1900	1900 VME-ppm : 800 1000 800	- VLE-mg/m3 : - 7200	- VLE-ppm : -	- Temps : -	-

8.2. Exposure controls

Personal protection measures, such as personal protective equipment

Use personal protective equipment that is clean and has been properly maintained.

Store personal protective equipment in a clean place, away from the work area.

Never eat, drink or smoke during use. Remove and wash contaminated clothing before re-using. Ensure that there is adequate ventilation, especially in confined areas.

- Eye / face protection

Avoid contact with eyes.

Use eye protectors designed to protect against liquid splashes

Before handling, wear safety goggles in accordance with standard EN166.

- Hand protection

Use suitable protective gloves that are resistant to chemical agents in accordance with standard EN374.

Gloves must be selected according to the application and duration of use at the workstation.

Protective gloves need to be selected according to their suitability for the workstation in question : other chemical products that may be handled, necessary physical protections (cutting, pricking, heat protection), level of dexterity required.

Type of gloves recommended :

- Nitrile rubber (butadiene-acrylonitrile copolymer rubber (NBR))

- PVA (Polyvinyl alcohol)

Recommended properties :

- Impervious gloves in accordance with standard EN374

- Body protection

Avoid skin contact.

Wear suitable protective clothing.

Suitable type of protective clothing :

In the event of substantial spatter, wear liquid-tight protective clothing against chemical risks (type 3) in accordance with EN14605 to prevent skin contact.

In the event of a risk of splashing, wear protective clothing against chemical risks (type 6) in accordance with EN13034 to prevent skin contact.

Work clothing worn by personnel shall be laundered regularly.

After contact with the product, all parts of the body that have been soiled must be washed.

- Respiratory protection

Avoid breathing vapours.

If the ventilation is insufficient, wear appropriate breathing apparatus.

When workers are confronted with concentrations that are above occupational exposure limits, they must wear a suitable, approved, respiratory protection device.

Type of FFP mask :

Wear a disposable half-mask aerosol filter in accordance with standard EN149.

Category :

- FFP1

Anti-gas and vapour filter(s) (Combined filters) in accordance with standard EN14387 :

- A1 (Brown)

Particle filter according to standard EN143 :

- P1 (White)

SECTION 9 : PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

General information :	
Physical state :	Fluid liquid.
	Spray.
Important health, safety and environmental information	
pH :	Not relevant.
Boiling point/boiling range :	Not relevant.
Explosive properties, lower explosivity limit (%) :	1.5
Explosive properties, upper explosivity limit (%) :	10
Vapour pressure (50°C) :	Not relevant.
Density :	0.66
Water solubility :	Insoluble.
Melting point/melting range :	Not specified.
Self-ignition temperature :	Not relevant.
Decomposition point/decomposition range :	Not specified.
Chemical combustion heat :	>= 30 kJ/g.
9.2. Other information	

No data available.

SECTION 10 : STABILITY AND REACTIVITY

10.1. Reactivity

No data available.

10.2. Chemical stability

This mixture is stable under the recommended handling and storage conditions in section 7.

10.3. Possibility of hazardous reactions

When exposed to high temperatures, the mixture can release hazardous decomposition products, such as carbon monoxide and dioxide, fumes and nitrogen oxide.

10.4. Conditions to avoid

Any apparatus likely to produce a flame or to have a metallic surface at high temperature (burners, electric arcs, furnaces etc.) must not be allowed on the premises.

Avoid :

- heating

- heat

10.5. Incompatible materials

10.6. Hazardous decomposition products

The thermal decomposition may release/form :

- carbon monoxide (CO)

- carbon dioxide (CO2)

SECTION 11 : TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects

Exposure to vapours from solvents in the mixture in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on kidney, liver and central nervous system.

Symptoms produced will include headaches, numbness, dizziness, fatigue, muscular asthenia and, in extreme cases, loss of consciousness.

Repeated or prolonged contact with the mixture may cause removal of natural oil from the skin resulting in non-allergic contact dermatitis and absorption through the skin.

Splashes in the eyes may cause irritation and reversible damage

Narcotic effects may occur, such as drowsiness, narcosis, decreased alertness, loss of reflexes, lack of coordination or dizziness.

Effects may also occur in the form of violent headaches or nausea, judgement disorder, giddiness, irritability, fatigue or memory disturbance.

11.1.1. Substances

Acute toxicity :

HYDROCARBURES, C6, ISOALCANES, <5% N-HEXANE Oral route : LD50 = 16750 mg/kg

Dermal route :

LD50 = 3350 mg/kg

11.1.2. Mixture

No toxicological data available for the mixture.

SECTION 12 : ECOLOGICAL INFORMATION

Toxic to aquatic life with long lasting effects.

The product must not be allowed to run into drains or waterways.

12.1. Toxicity

12.1.1. Substances

HYDROCARBURES, C6, ISOALCANES, <5% N Fish toxicity :	I-HEXANE LC50 = 18.3 mg/l Species : Oncorhynchus mykiss Duration of exposure : 96 h
Crustacean toxicity :	EC50 = 31.9 mg/l Species : Daphnia magna Duration of exposure : 48 h
Algae toxicity :	ECr50 = 3 mg/l Species : Pseudokirchnerella subcapitata Duration of exposure : 72 h
1R-TRANS-PHENOTHRINE (CAS: 26046-85-5) Fish toxicity :	LC50 = 0.0027 mg/l Species : Salmo gairdneri Duration of exposure : 96 h

0,0001 < NOEC <= 0,001 mg/l

	Factor $M = 100$
Crustacean toxicity :	EC50 = 0.0043 mg/l Species : Daphnia magna Duration of exposure : 48 h
	0,0001 < NOEC <= 0,001 mg/l Factor M = 100
Algae toxicity :	ECr50 = 0.011 mg/l Species : Pseudokirchnerella subcapitata Duration of exposure : 72 h
	0,0001 < NOEC <= 0,001 mg/l Factor M = 100
12.1.2. Mixtures	
No aquatic toxicity data available for the mixture.	
12.2. Persistence and degradability	
12.2.1. Substances	
1R-TRANS-PHENOTHRINE (CAS: 26046-85-5) Biodegradability :) no degradability data is available, the substance is considered as not degrading quickly.
HYDROCARBURES, C6, ISOALCANES, <5% Biodegradability :	N-HEXANE Rapidly degradable.
12.3. Bioaccumulative potential	
12.3.1. Substances	
HYDROCARBURES, C6, ISOALCANES, <5%	
Octanol/water partition coefficient :	$\log \text{Koe} = 3.6$
Bioaccumulation :	BCF = 501.187
12.4. Mobility in soil No data available.	
12.5. Results of PBT and vPvB assessment	
No data available.	
12.6. Other adverse effects	
No data available.	

No data available.

SECTION 13 : DISPOSAL CONSIDERATIONS

Proper waste management of the mixture and/or its container must be determined in accordance with Directive 2008/98/EC.

13.1. Waste treatment methods

Do not pour into drains or waterways.

Waste :

Waste management is carried out without endangering human health, without harming the environment and, in particular without risk to water, air, soil, plants or animals.

Recycle or dispose of waste in compliance with current legislation, preferably via a certified collector or company.

Do not contaminate the ground or water with waste, do not dispose of waste into the environment.

Soiled packaging :

Empty container completely. Keep label(s) on container.

Give to a certified disposal contractor.

SECTION 14 : TRANSPORT INFORMATION

Transport product in compliance with provisions of the ADR for road, RID for rail, IMDG for sea and ICAO/IATA for air transport (ADR 2015 - IMDG 2014 - ICAO/IATA 2015).

14.1. UN number

1950

14.2. UN proper shipping name

UN1950=AEROSOLS, flammable

14.3. Transport hazard class(es)

- Classification :



2.1

14.4. Packing group

14.5. Environmental hazards

- Environmentally hazardous material :



14.6. Special precautions for user

ADR/RID	Class	Code	Pack gr.	Label	Ident.	LQ	Provis.	EQ	Cat.	Tunnel
	2	5F	-	2.1	-	1 L	190 327 344 625	E0	2	D
								_		
IMDG	Class	2°Label	Pack gr.	LQ	EMS	Provis.	EQ			
	2.1	See SP63	-	SP277	F-D,S-U	63 190 277 327	E0			
						344 959				
	•							-		
IATA	Class	2°Label	Pack gr.	Passager	Passager	Cargo	Cargo	note	EQ	
	2.1	-	-	203	75 kg	203	150 kg	A145	E0	
					_		-	A167		
								A802		
	2.1	-	-	Y203	30 kg G	-	-	A145	E0	
								A167		
								A802		

For limited quantities, see part 2.7 of the OACI/IATA and chapter 3.4 of the ADR and IMDG.

For excepted quantities, see part 2.6 of the OACI/IATA and chapter 3.5 of the ADR and IMDG.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

No data available.

SECTION 15 : REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

- Classification and labelling information included in section 2:

The following regulations have been used:

- Directive 75/734/CEE modified by directive 2013/10/UE
- EU Regulation No. 1272/2008 amended by EU Regulation No. 487/2013.
- EU Regulation No. 1272/2008 amended by EU Regulation No. 758/2013.
- EU Regulation No. 1272/2008 amended by EU Regulation No. 944/2013.
- EU Regulation No. 1272/2008 amended by EU Regulation No. 605/2014.
- EU Regulation No. 1272/2008 amended by EU Regulation No. 1297/2014.

- Container information:

No data available.

- Particular provisions :

No data available.

- Labelling for biocidal products (Regulation 1896/2000, 1687/2002, 2032/2003, 1048/2005, 1849/2006, 1451/2007 and Directive 98/8/EC)

Name	CAS	%	Product-type
D-TRANS-TETRAMETHRINE	1166-46-7	0.95 g/kg	18
S-METHOPRENE	65733-16-6	0.12 g/kg	18
1R-TRANS-PHENOTHRINE	26046-85-5	1.20 g/kg	18

Product-type 18 : Insecticides, acaricides and products to control other arthropods.

15.2. Chemical safety assessment

No data available.

SECTION 16 : OTHER INFORMATION

Since the user's working conditions are not known by us, the information supplied on this safety data sheet is based on our current level of knowledge and on national and community regulations.

The mixture must not be used for other uses than those specified in section 1 without having first obtained written handling instructions.

It is at all times the responsibility of the user to take all necessary measures to comply with legal requirements and local regulations.

The information in this safety data sheet must be regarded as a description of the safety requirements relating to the mixture and not as a guarantee of the properties thereof.

Modifications brought with regard to the previous version :

- classification

- section 3.

Wording of the phrases mentioned in section 3 :

H220	Extremely flammable gas.
H225	Highly flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H336	May cause drowsiness or dizziness.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.

Abbreviations :

ADR : European agreement concerning the international carriage of dangerous goods by Road.

IMDG : International Maritime Dangerous Goods.

IATA : International Air Transport Association.

ICAO : International Civil Aviation Organisation

RID : Regulations concerning the International carriage of Dangerous goods by rail.

WGK : Wassergefahrdungsklasse (Water Hazard Class).

GHS02 : Flame

GHS07 : Exclamation mark

GHS09 : Environment

PBT: Persistent, bioaccumulable and toxic.

vPvB : Very persistent, very bioaccumulable.

ure

SVHC : Substances of very high concern.